

## DM Dispenser Type Flat-High Series

### Technicality

		DM-DISFM-H01	DM-DISFM-H02	DM-DISFM-H04
Grades		1	1	1
No of nozzles		1	2	4
Simultaneous fillings		1	2	4
Meter Type		Mechanic	Mechanic	Mechanic
Capacity Max.	Lt/Min (kg/min)	50 ( 27,5 )	50 ( 27,5 )	50 ( 27,5 )
Capacity Min.	Lt/Min (kg/min)	5 ( 2,75 )	5 ( 2,75 )	5 ( 2,75 )
Hose (4.2 m)	INCH	1/2"	1/2"	1/2"
Operating Temperature	(°C)	-25+55	-25+55	-25+55
Relative humidity	(%)	100	100	100
Supply voltage	(V)	230	230	230
Frequency	(Hz)	50	50	50
Electronic units power	(W)	100	100	100
<b>Dimensions (W x L x H)</b>	(mm)	900 x 500 x 1850	900 x 500 x 1850	900 x 500 x 1950
<b>Weight</b>	(Kg)	150	190	270
Amount/Volume programming		money/liter	money/liter	money/liter
Emergency stop		1	1	1
Sight glass		NO	NO	NO
Nozzle swivel		YES	YES	YES
Breakaway coupling		3/4"	3/4"	3/4"
Filter		YES	YES	YES
Manometer		YES	YES	YES
		DM-DISFD-H01	DM-DISFD-H02	
Grades		1	1	
No of nozzles		1	2	
Simultaneous fillings		1	2	
Meter Type		Mass Flow	Mass Flow	
Capacity Max.	(kg/h)	6500	6500	
Capacity Min.	(kg/h)	0	0	
Hose (4.2 m)	INCH	1/2"	1/2"	
Operating Temperature	(°C)	-25+55	-25+55	
Relative humidity	(%)	100	100	
Supply voltage	(V)	230	230	
Frequency	(Hz)	50	50	
Electronic units power	(W)	100	100	
<b>Dimensions (W x L x H)</b>	(mm)	900 x 500 x 1850	900 x 500 x 1850	
<b>Weight</b>	(Kg)	150	190	
Amount/Volume programming		money/liter	money/liter	
Emergency stop		1	1	
Sight glass		NO	NO	
Nozzle swivel		YES	YES	
Breakaway coupling		3/4"	3/4"	
Filter		YES	YES	
Manometer		YES	YES	